

Ink

Solvent Base

RUB Series

FIELD OF APPLICATION

Substrates

The screen printing ink RUB is excellently suited to print onto

PU leather

PVC leather

Genuine leather

EVA (Split, Molded, Skin)

TPU

Polyester

Water Proof Nylon

Nylon

Field of Use

RUB series is designed to print on Flip flop, Hawaii Chappal, Molded EVA Sleeper, EVA Sandals, EVA Shoes, EVA Yoga Mat, EVA Toys, Backpack.

The ink can be used as 1 or 2 component ink.

This special ink has compared to other 2 component inks, a very good adhesion to the substrate and is highly qualified for footwear standard.

RUB can also be processed with spray gun, drawing brush on EVA material. In order to avoid surface irregularities, we recommend to filter the thinned ink (25 microns screen) before processing.

CHARACTERISTICS

This glossy, physically drying and chemical reactive screen printing ink exhibits good mechanical & chemical resistance as well as good flexibility and adhesion. Excellent printability and stable in color matching.

HOW TO USE

Apply EVA Primer 2303 to EVA substrate by wiping to improve the mechanical strength of the ink. Dilute the ink with 10%-20% TP-65 (slow dry thinner) or TP-69 (medium dry thinner). Use TP-67 to make the drying slower. You may add Hardener H/ 9004 Hardener to improve the mechanical strength of the ink on substrate.

For Synthetic and Genuine leather always advisable to use as 2 component ink. Some PU material needs post treatment after printing.

RUB is designed to dry slowly in order to avoid clogging.

For overprinting, the next color is printed only after tack free..

Mesh Recommended- 40T-120T

Tack Free Time	5-10 minutes	Natural Cure
Hard Drying Time	6-8 hours	Natural Cure

If several layers are printed longer drying time is recommended

CLEANER

Use TP-65 for cleaning the screen /washing up.

RANGE OF COLORS

Basic Colors

100 Transparent

105 H.D. White

201 Deep Yellow

203 Original Yellow

206 lemon yellow

300 Rose Red

3020 Dark Red
3038 Light Resistant Magenta
304 Bronze Red
305 Orange
401 Violet
403 Original Blue
404 Ultra Marine
408 Emerald Blue
501 Black
601 Green
701 Brown

Fluorescent Colors

131 Fluorescent Yellow
133 Fluorescent Red
134 Fluorescent Orange
140 Fluorescent Green
148 Fluorescent Blue
141 Fluorescent Violet

Metallic Colors

801 Silver
901 Pale Gold
902 Rich Gold

4 Color Process Printing inks

Process Black
Process Red
Process Yellow
Process Blue

ADDITIVES

Thinner:

Before production, the viscosity of the screen printing has to be adjusted by the addition of thinner.

Thinner, very fast (addition 15%-25%)

TP-61

Thinner, standard (addition 15%-25%)

TP-65

Retarder:

Thinner, slow(addition 15%-20%)
TP-67

Retarder TP-67 can be used along with TP-65 or TP-61 to meet the printing requirement.

Hardener

Prior to printing hardener must be added in correct quantity and always by weight and mixture must be stirred thoroughly.

Hardeners are sensitive to humidity and always to be stored in a sealed container.

Hardener 9004 is the standard hardener -H

The two different ratios are

- 1) 5% Hardener 9004/ H 20 parts by weight of ink + 1 part of hardener by weight
- 2) 10% Hardener 9004/ H 10 parts by weight of ink + 1 part of hardener by weight

The second variation must be applied if high resistance (e.g. dry & wet Test) is required.

Custom Colors

Pantone/RAL/TPX colors are custom made colors and can be developed as per request.

TYPE OF PACKING

1-kg Can

SHELF LIFE

Shelf life depends on the reactivity of the ink

while adding hardener as well as storage conditions(temperature).

The shelf life for an unopened ink container if stored in a dark room at a temperature of 15°-25° C is

- 1) 2 years for the basic colors and Process colors
- 2) 1 year for Metallics and fluorescent colors.

Under different conditions, particularly higher storage temperatures, the shelf life is reduced .In such case,the warranty given by Spinks expires.

PRECAUTION

- 1) Hardener 9004/H is the standard hardener .At room temperature 20°25°C a pot life is 4-5 hours. If temperature is higher shelf life of the ink will reduce.
- 2) Ink is glossy .Matt ink can be developed on request.
- 3) As PVC doesn't have good solvent resistance, it may cause tackiness problem while stacking Nylon material with PVC laminated from backside, make sure finished products are dried thoroughly and avoid stacking together. When printing on Nylon with backside laminated PVC, it is easy to cause color transformation, to solve this problem, use color with good penetration resistance.
- 4) Please refer MSDS before use.
- 5) Be sure to do trials before commercial run to confirm that the product fits the purpose
- 6) Additional technical information may be obtained from our Technical Department.
- 7) All characteristics described in this Technical Data Sheet refer exclusively to the standard products listed under range, provided that they are processed in accordance with the intended use and only when used with

the recommended additives. The selection and testing of the ink for specific applications is exclusively your responsibility. Should, however, any liability claims arise, they shall be limited to the value of the goods delivered by us and utilized by you with respect to any and all damages not caused intentionally or by gross

Properties	
Items	Performance
Adhesion	Excellent
Transfer resistance	Grade 4-5
Scratch Resistance	Grade 4-5
Anti-attribution	Grade 4-5
Kneadability	Grade 5
Acid Resistance	Grade 3-4
Alkali Resistance	Grade 3-4
Water Resistance	Grade 3-4

Technical Parameters	
Items	Performance
Appearance	Refer to color sample
Chroma	8%-15%
Thinness	Less than 7 microns
Viscosity	100-180P
Glossiness	70-75
Flowability	15-20mm/s
Resin	>45%